

PLATINUM CLASSIC LINE



PLATINUM CLASSIC **SEMISYNTHETIC 10W-40**

Quality class: API: SL/SJ/CF

ACEA: A3/B3

Viscosity grad: SAE: 10W-40

GENERAL FEATURES:

Semi-synthetic, all-season engine oil based on a modern formulation which, besides base oils, contains an up-to-date, perfectly matched package of improvers. The technology, which has been used, allows excellent oil parameters to be obtained and reduces the risk of excessive valve wear, at the same time ensuring better buildup control.

It guarantees:


- effective engine protection and cleanness by keeping soot in a suspension,
- failure-free engine operation during start-up in difficult conditions,
- proper antiwear protection level for engine components,
 slowed down ageing processes,
- extended engine life.

APPLICATION:

PLATINUM CLASSIC SEMISYNTHETIC 10W-40 is designed for all-year-round use in petrol or diesel fuel operated automobile engines. Owing to its excellent formulation, guaranteeing outstanding parameters, this oil may be successfully used in lightweight delivery trucks and vans as well. This oil may be used in both new and older type engines which have been operated for a few years and are characterised by higher mileage, for which manufacturers recommend lower grade oils. Owing to the unique

CPF technology, the oil ensures excellent engine work in all conditions: while running in traffic jams, normal traffic, and longer journeys.

The high quality of the oil is confirmed not only by its improved technology, but also by satisfying the requirements of Mercedes-Benz 229.1.





PLATINUM CLASSIC LINE

STANDARDS, APPROVALS. SPECIFICATION:

Meet requirements: Mercedes - Benz 229.1

| PARAMETERS | UNIT | TYPICAL VALUES |
|------------------------------|-------|-------------------|
| SAE viscosity grade | - | 10W-40 |
| kinematic viscosity at 100°C | mm²/s | 14.5 |
| viscosity index | - | 157 |
| pour point | 0C | -33 |
| flash point | 0C | 232 |

NOTE: Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

